



DESCRIPTION:

HST PVC Sleeving is specially formulated to give high quality and value for money. Rated at 105°C, heat stabilized, it has good flame retardancy and meets the general requirements of UL224. Supplied in coils.

SPECIFICATION:



MATERIAL: PVC

COLOUR: Green/Yellow

OPERATING TEMPERATURE: -30°C to +105°C (store away from direct sunlight and below 25°C.)

SHRINK TEMPERATURE: 135°C

SHRINK RATIO: 2:1

ELONGATION AT BREAK: 220%

TENSILE STRENGTH: 19 MPa

FLAMMABILITY: Self-Extinguishing

APPROVALS: UL224, RoHS compliant

PART NUMBERS:

DIMENSIONS (mm)

PART NUMBER	MIN. SUPPLIED DIAMETER	RECOVERED DIAMETER	NOM. RECOVERED WALL	COIL LENGTH (m)
COILS				
HST 32 GREEN/YELLOW	3.2	1.6	0.45	100
HST 48 GREEN/YELLOW	4.8	2.4	0.50	100
HST 64 GREEN/YELLOW	6.4	3.2	0.60	100
HST 95 GREEN/YELLOW	9.5	4.8	0.60	100
HST 127 GREEN/YELLOW	12.7	6.4	0.65	50
HST 160 GREEN/YELLOW	16.0	8.0	0.80	50
HST 190 GREEN/YELLOW	19.0	9.5	0.80	50
HST 254 GREEN/YELLOW	25.4	12.7	1.00	30
HST 320 GREEN/YELLOW	32.0	16.0	1.00	30
HST 381 GREEN/YELLOW	38.1	19.0	1.00	30

Tel: +44(0) 1793616700 • Fax: +44(0) 1793 644304
 uksales@is-rayfast.com • export@is-rayfast.com

www.is-rayfast.com

2 Lydiard Fields, Swindon, Wiltshire, SN5 8UB

