

Non-Shrink Tubing

UL-Y

UL Approved PVC Sleeve
Non-shrink, insulating sleeves

COLD
Applied



1 This UL approved PVC sleeve is rated by Underwriters Laboratories at 300v. It is highly flame retarded and passes VW1 flame test. It is also approved to UL 224

Features & Benefits

- Passes VW1
- UL 224, file E183946
- Available in various colours

Operating Temperature

- From -40°C to +105°C

Ideal for insulating wire in areas of high temperatures

Specifications & Approvals

- UL224 File No. E183946
- Passes VW1 flame test specification

Internal Dia.	Nominal Wall	Spool Size	Part Number
As Supplied (mm)	mm	m	
1.0	0.4	100	UL-Y-1.0-M300-Colour
1.5	0.4	100	UL-Y-1.5-M300-Colour
2.0	0.4	100	UL-Y-2.0-M300-Colour
2.5	0.4	100	UL-Y-2.5-M300-Colour
3.0	0.5	100	UL-Y-3.0-M300-Colour
4.0	0.5	100	UL-Y-4.0-M300-Colour
5.0	0.5	100	UL-Y-5.0-M300-Colour
6.0	0.5	100	UL-Y-6.0-M300-Colour
7.0	0.5	100	UL-Y-7.0-M300-Colour
8.0	0.6	100	UL-Y-8.0-M300-Colour
9.0	0.6	100	UL-Y-9.0-M300-Colour
10.0	0.6	100	UL-Y-10.0-M300-Colour
12.0	0.6	100	UL-Y-12.0-M300-Colour
14.0	0.7	100	UL-Y-14.0-M300-Colour
16.0	0.7	100	UL-Y-16.0-M300-Colour
20.0	0.8	100	UL-Y-20.0-M300-Colour
25.0	0.8	100	UL-Y-25.0-M300-Colour

Colours Available

