

A. System Overview



Corrugated Tubing Holder with Push Mount


B1. Cable Ties

- Use to secure and route all standard sizes of solid wall or slit corrugated loom tubing
- Ribs prevent lateral movement of corrugated loom tubing along the mount

- Rugged clip prevents accidental disassembly of tubing due to shock or vibration

B2. Cable Accessories

B3. Stainless Steel Ties



C1. Wiring Duct

C2. Surface Raceway

C3. Abrasion Protection

C4. Cable Management

| Part Number | Nominal Diameter A | | Max. Panel Thickness | | Panel Hole Diameter | | Std. Pkg. Qty. | Std. Ctn. Qty. |
|--------------|--------------------|----|----------------------|-----|---------------------|-----|----------------|----------------|
| | In. | mm | In. | mm | In. | mm | | |
| CTH19U04-C30 | 0.19 | 5 | 0.125 | 3.2 | 0.386 | 9.8 | 100 | — |
| CTH35U08-C30 | 0.35 | 9 | 0.125 | 3.2 | 0.386 | 9.8 | 100 | 500 |
| CTH38U10-C30 | 0.38 | 10 | 0.125 | 3.2 | 0.386 | 9.8 | 100 | — |
| CTH50U13-C30 | 0.50 | 13 | 0.125 | 3.2 | 0.386 | 9.8 | 100 | — |
| CTH62U17-C30 | 0.62 | 17 | 0.125 | 3.2 | 0.386 | 9.8 | 100 | — |
| CTH87U22-C30 | 0.87 | 22 | 0.125 | 3.2 | 0.386 | 9.8 | 100 | — |

D1. Terminals

Harness Clips



D2. Power Connectors

D3. Grounding Connectors

E1. Labeling Systems

- Integral "spring" holds wire bundles tightly
- Available in vertical and horizontal loading configurations

- Design of wing provides added stability



E2. Labels

E3. Pre-Printed & Write-On Markers

| Part Number | Max. Bundle Diameter Range | | Max. Panel Thickness | | Panel Hole Diameter | | Material | Color | Mounting Method | Std. Pkg. Qty. | Std. Ctn. Qty. |
|---------------|----------------------------|------------|----------------------|-----|---------------------|-----|-----------|-------|-----------------|----------------|----------------|
| | In. | mm | In. | mm | In. | mm | | | | | |
| HCMP06B12-C20 | .24 - .47 | 5.9 - 12.5 | .118 | 3.0 | .25 | 6.4 | Nylon 6.6 | Black | Push Mount | 100 | 500 |
| HCMP06C12-C20 | .24 - .47 | 5.9 - 12.5 | .105 | 2.7 | .25 | 6.4 | | | | 100 | 500 |

E4. Permanent Identification

E5. Lockout/Tagout & Safety Solutions

F. Index

Tel: +44(0) 1793616700 • Fax: +44(0) 1793 644304
 uksales@is-rayfast.com • export@is-rayfast.com
www.is-rayfast.com
 2 Lydiard Fields, Swindon, Wiltshire, SN5 8UB

